

BFR-M700

Biometric Fingerprint Reader



Function:

- TCP/IP, RS232/485 communication and USB Host.
- 3.0 inch TFT touch screen, T9 Input, 9 Digit User ID.
- 2 user-defined function keys, left for door belling, right for shift of identification mode.
- Infra-red optical system enables user-identification in poorly lit environments.
- 50 time zones, 99 groups and 10 unlock combinations, anti-pass back and dismantle function.

Specification:

Model	BFR-M700
CPU	Multi-Bio CPU 630Mhz
Memory	256M Flash, 64M SDRAM
Fingerprint Sensor	Optical Sensor
Camera	High Resolution Infrared camera
Display	3 Inch Touch Screen
Face Capacity	400 (Optional 3000)
Fingerprint Capacity	2000 (Optional 5000)
ID Card Capacity	10,000 (Optional Function)
Logs Capacity	10,000
Communication	TCP/IP, RS232/485, USB Host
Access Control Interfaces for Wiegand Signal	3 rd party electric lock, door sensor, alarm, wired bell and exit button Wiegand in and out
Power Supply	12V/3A
Verification Speed	2Sec
Operating Temperature	0-45
Operating Humidity	20% - 80%
Dimensions	275(L)*100(H)*195(W) mm
Gross Weight	0.87 Kg