

## Recording Server

**EV-4S210**



### Specification:

Model	EV-4S210
<b>Form Factor</b>	
1U Rack Mount	
<b>Dimensions</b>	
WxHxD (Inch) 17.24 x 1.7 x 28.7	
W x H x D (mm) 438 x 43 x 728	
<b>Storage Option 2: 4x 3.5" hot-plug</b>	
<b>Expansion Slot Option 1 (default): One x16 PCIe 3.0, FHHL</b>	
<b>Front I/O Option 1: None Option 2: 2x USB 2.0 ports</b>	
<b>Power Supply</b> High efficiency fixed 400W PSU, 80 Plus	
<b>Fan</b> 5x system fans	
<b>System Management</b> IPMI v2.0 Compliant, on board "KVM over IP" support	
<b>Operating Environment</b> Operating temperature: 5°C to 35°C (41°F to 95°F) Non-operating temperature: -40°C to 65°C (-40°F to 149°F) Operating relative humidity: 50% to 85%RH. Non-operating relative humidity: 20% to 90%RH	
<b>Processor</b> Intel® Xeon® processor E5-2600, E5-2600 v2 product family <b>Max. TDP Support 135W</b>	
<b>Memory: Total Slots 16</b>	
<b>Capacity</b> Up to 256GB RDIMM	
<b>Memory Type</b> 1866/1600/1333 MHz DDR3 RDIMM	
<b>Memory Size</b> 16GB, 8GB RDIMM	
<b>Network Controller LOM</b> Intel® I350 dual-port 1 GbE Dedicated 1 GbE management port	
<b>Storage Controller Onboard</b> Intel® 602: 4x SATA 3Gb/s ports 2x SATA 6Gb/s ports	
SATA RAID 0, 1, 5, 10	
<b>Onboard Storage</b> Support 1x SATADOM	
<b>Rear I/O</b> 4x USB 2.0 ports 1x VGA port 1x RS232 serial Port 2x 1 GbE RJ45 port 1x GbE RJ45 management port	