



NV-ODR7035N

Function:

- 1/2.5" - 3 Megapixel CMOS
- 2 Megapixel Real-time
- TI DaVinci DSP DM368
- Weatherproof Aluminium Housing
- Support ONVIF, PoE
- HD video, 1080P(1920*1080) real-time
- 3-Axis cable built-in bracket
- Low LUX: OLUX (IR on)
- IR CUT Filter
- With Mounting stand

**Outdoor Weather proof HD IP Camera
3 Megapixel - POE (2 MP Real-time)**

IK-10 Vandal Proof & IP66 Weather-proof

Specification:

Model	NV-ODR7035N
Image Sensor	1/2.5" 3.0 Megapixel CMOS Image sensor, low illumination, (2 Megapixel Real-time) Wide Dynamic Range(WDR - 120db)
System Structure	Embedded LINUX RTOS ,Dual core 32 bits DSP (TI Davinci DM368), Pure hardwarecompression, watchdog, 32M Flash, 128M DDR2
Resolution	MainStream: 1920×1080,1600×1200,1280×1024, 1280×960,1024×768,1280×720 Sub Stream: 352×192,320×192,288×192,256×192
Frame Rate	3.Mega-20 fps; 2Mega or below-25 fps(Real-time)
Lens	Varifocal 3-8mm
IR LED	4 Array LED's – 60 Mtr IR Distance
Video	Dual Streaming, AVI format
Network Port	1 RJ45 10/100M self-adaptive
Network	FTP/PPPOE/DHCP/DDNS/NTP/UPnP/ONVIF 2.0, etc.
Video Compression	H.264
Min. Illumination	Color: 0.1 lux, F1.0, B/W: 0.02 lux, F1.0
Day & Night	With IR Cut Filter
POE	Support PoE
Dimension	390(W)x100(H)x110(D)mm
Weight	3.1 Kg