



### Function:

- H.264 Main Profile compression standard
- Higher compression ratio
- Compatible with IPC, IP PTZ Camera
- Network Video Server, Support Onvif protocols.
- VGA, HDMI output synchronization, up to 1080P
- Image position can be adjusted to the order
- More convenient operating with tree menu
- Two different colours desktop
- Can achieve 15 times zoom with mouse roller, magnified images can easily drag (preview, playback, remote access)
- Can focus the IP PTZ camera with mouse roller.
- Capture and check easy.
- Capture can be stored in a separate area
- Time column display of playback
- Backup precisely to seconds, and the period can be set
- The backup files can be played directly on the NVR
- Support 3G and WIFI
- The resolution can be adjusted
- Intelligent analysis of HDD
- Automatically skip bad sectors and continue to record

### Specification:

Model	NVR-915304-N6
Operation System	Embedded LINUX operation system
Graphic encoding control	The quality of the images can be adjusted; Variable Stream and Fixed Stream optional
Dual-stream	Dual-stream can be set for each channel
Video Standard	NTSC: 1080P(1920×1080), 30 f/s; 720P(1280×720), 30f/s. PAL : 1080P(1920×1080), 25 f/s; 720P(1280×720), 25f/s.
Resolution	1080P(1920×1080) / 720P(1280×720)
Motion Detection	Detection areas can be set for each channel, at 6 sensitivities
Playback Resolution	Playback synchronously at the resolution of 1080P/720P for any 4 channels
Mask Setting	Support 4 masks for each channel
Recording Type	Support manual, automatic, motion-detection, alarm-triggered recording modes
Backup Type	Support flash, USB HDD, USB burner, Network recording and backup
Operation mode	Panel, Mouse, Remote
Login	ID and Password
Video Storage	HDD and Network
Audio Input	4 channels audio input
Video Output	1*VGA+1*HDMI
Network Interface	1*RJ45,10M/100M/1000M self-adaptive
RS485 Interface	Latest 485 interface, Receiving and transmitting two-way simultaneous; Support 19 PTZ protocols
USB port	3*USB 2.0 ports
Alarm In & Out	4 channels
Wireless Interface	3G / WIFI
HDD Support	Support 6 HDDs, each up to 3TB
Mobile Surveillance	Support All Smart Phones Base On The System iPhone, Android, Windows Mobile, Symbian
Power Supply	DC12V/5A (support 2 HDDs); ATX110-220V,250W,50-60Hz (support 6-9 HDDs)
Power Consumption	≤30W (without HDDs)
Working Temperature	-10 ~ +55
Working Humidity	10%-90%
Dimension	Without Package: 440mm×370mm×68mm, With package: 535mm×465mm×165mm
Weight (without HDD)	Net Weight: 5.5 Kg; Gross Weight: 7.5 Kg
Packing	2 pcs in one packet. Carton Dimm.: 535mm×465mm×350mm ; Carton Weight: 16 Kg
Installing	Embedded or Desktop