

# SEECAM

Leading UK Brand..



## NVR-AXBS0508

### Function:

- Stable, effective and secure, applicable to various network
- 16ch video input, Support IPC, Can access to both IPC and DVS
- Support Dual streaming.1080P,960P,720P,D1,CIF,QCIF resolution
- VGA , HDMI and DVI port, Support 1920×1080 display.
- High quality record, Support 2ch video Synchronous playback
- Built in system disk and DOM disk, Easy for installation and maintenance upgrade
- Support picture capture and electronic map
- Mouse, keyboard, remote-client control
- Can be used with the centralized management platform software (CMS) for unified control and forward data as Sub Centre

### Specification:

Model	NVR-AXBS0508
Video Input No.	16 Channel
RAID -HDD No.	8×SATA(Hot Plug) RAID 0/1/5/10 Support
System	WIN7 System, INTEL XEON CPU,4GB Cache memory, watch dog
Input Equipment	IP Camera (IPC) , Video Server(DVS)
Transmission Mode	LAN
Video Decode	H.264/MPEG-4
Resolution	2592X1920,2048X1536,1920×1080,1280×960, 1280×720, 704×576 352×288, 176×144
Video Frame Rate	1-25fps
Video Code Rate	500kpbs~8Mpbs
Video OutputPort	HDMI×1,VGA×1, DVI×1
Output Resolution	1024×768~1920×1080
Network Port	RJ45 Port, 100/1000M self adaption
PTZ Control	Support multi protocol, Rs232/485, speed dome control procedure
Network Protocol	TCP/IP,UDP,FTP,HTTP,DHCP,DDNS
Security Protection	Multiple password protection, Any authority distribution
Power Supply	AC100V~240V,50HZ/60HZ
Working Temperature	0°C ~ 60°C
Working Humidity	10%-85%
Packing size	W795*D590*H212