

IP PTZ Camera



SE-IPS7810I

**2.0 Mega Pixel Real Time IP PTZ
18X Optical Zoom**

IK-10 Vandal Proof & IP66 Weather-proof

Specification:

Model	SE-IPS7810I
System Structure	Embedded LINUX RTOS ,Dual core 32 bits DSP (TI Davinci DM368), Pure Hardware compression, watchdog, 32M Flash, 128M DDR2.
IR LED & Range	10 pcs of High power dot matrix IDS intelligent IR LEDS- 120M
Ethernet	10Base -T, /100Base-TX, RJ45 Connector
Max. Image Resolution	1920×1080,1280×720 and Dual Stream Support
Optical Zooming	18X
Frame Rate	PAL :25 fps NTSC: 30 fps
Image Compression	H.264
Protocols	TCP/IP, HTTP, DHCP, DNS, RTP/RTCP, RTSP, PPPoE, SMTP, NTP (FTP, SNMP optional)
Pan Range / Speed	360° endless , Pan manual speed: 0.1° ~ 200°/s, Pan Preset speed -250°/S
Tilt Range / Speed	-5° ~ 92° (auto flip) / 0.01~120°/S
Number of Preset	255
RS-485 Protocols	A, Pelco-P, Pelco-D, self-adaptive
Working Temperature/Humidity	-30°C ~ 65°C (-22° F ~ 149° F), 90% or less
Protection Level	IP66 with TVS 4000V lightning protection, IK10 Vandal Proof Casing
Power Supply	12V/DC (24V/AC optional) / 40W MAX
Dimensions	Φ230(mm)×348(mm)
Net Weight	5.0Kg (11.02lbs)